Coda Floodlight




CODA 500W Floodlight


- ☐ One, three and four compartment cyclorama floodlights with asymmetric distribution
- ☐ For even coverage of backcloths and cycloramas up to 20' high
- ☐ Wide, asymmetric distribution
- ☐ Supplied in black finish with color frame, integral wire guard, yoke and one 3' cable per compartment with bare ends




Coda 500W



Coda 500W/3



Coda 500W/4



Weights and dimensions

•	Coda	Coda	Coda	
	500/1	500/3	500/4	
Weight	81/2 lb	18¹/₂ lb	24 lb	
Packed weight	10 lb	20 lb	251/2 lb	
Packed volume	1.05 cu ft	2.75 cu ft	3.6 cu ft	
Filter out size	81/2" v 91/2"			



Coda Floodlight



Strand Theatre Lighting

Operational features

Lamp access

Through the front of each unit or compartment via hinged wireguard with positive spring retention clip

Tilt/Pan

Heat insulated hand knob on right side of luminaire.

Electrical & mechanical data Construction

Pressure diecast zinc alloy end sections common to all luminaires joined by machine threaded screws to pressed sheet steel housing. High temperature stoved epoxy powder coat in black.

Anchorage provided for safety cable.

Mounting and suspension

Single units: Fork of aluminum alloy, reversible, with 2³/₄" diameter friction disk and heat insulated hand knob. Fitted with reversible 'L' forks, dual top suspension fork/groundrow tilt foot each with 2³/₄" diameter friction disk and hand knob.

Supply voltage

120V 50/60 Hz

Standards

Designed to conform to EN 60-598 2-17

Ordering information

Coda 500

Wide-angle 500W floodlight in single, 3 or 4 compartment units for even top or bottom lighting of up to 20' cycloramas when used 41/2' from backdrop, and on 41/2' centres.

Cat. No. Description

14111		500W cyclight, bar	e
	laade		

14131 Coda 500/3 500W, 3-unit cyclight, 3 bare leads

14141 Coda 500/4 500W, 4-unit cyclight, 4 bare leads

Optional Accessories

Cat. No. Description

18123 Additional color frame, 500W

82019 Standard 2" pipe C-clamp with stud (required for hanging)

82003 Safety cable 19", light duty

Photometric data

Typical performance based on 500W FDN lamp

At 6' hanging. 45° angle. 41/2' from cyclorama on 41/2' centers

Coda

Cyc Heigh	nt (yds)	1		2	3	4	5	6
500W		19		30	39	40	40	28
	Distance (yd)	1	2	3	4	5	6	
	Beam Ø (yd)	1.2	2.4	3.6	4.8	6	7.3	
	IIIum (FC)	392	95	44	24	16	11	

Strand Lighting Inc

6603 Darin Way, Cypress, CA 90630, USA Tel: +1 714 230 8200 Fax +1 714 230 8173

Strand Lighting (Canada) Inc/Eclairages Strand (Canada) Inc

2430 Lucknow Drive No 15 Mississauga Ontario L5S 1V3 Canada Tel: +1 905 677 7130 Fax: +1 905 677 6859



The Company reserves the right to make any variation in design or construction to the equipment described.

© Strand Lighting Ltd. 2002

Strand™, Strand Lighting™, Strand Quartzcolor™ are trademarks of Strand Lighting Limited and Strand Lighting Inc.