



PATENTED

CITYCOLOR 400

Technical features

- Lamp

2 x Discharge MasterColour CDM-T 150W/830
or CDM-T 150W/942 (PHILIPS)

Color temperature: 3.000° K (CDM-T
150W/830) or 4.200° K (CDM-T 150W/942)
Average lamp life: 6.000 hours
Luminous flux: 2 x 14.000 lm
Burning position: Universal

- OPTIC COLOUR SYSTEM

Full CYM color mixing, unlimited variety of
colours and shades
High resolution stepper motors

- BEAM ANGLE

Beam angle (50%): 45°

- IP RATE

IP 66

- control input

Standard interface: RS-485; opto-couplet input
Protocol: USITT DMX 512

- AUTOMODE

Stand-alone control: auto mode function
master/slave (synchro mode) with 30
programs

- power supply

Rated voltage: 230V/50Hz-230V/60Hz
Rated power: 500Va
Rated current: 2,42A (230V)

- FUSES

Lamp fuse: 5.0A/250V (delay time)
Electronic fuse: 2.0A/250V (delay time)

DMX listing

DMX CHANNEL	FUNCTIONS
1	MOTOR SPEED
2	CYAN
3	YELLOW
4	MAGENTA
5	DIMMER
6	BASIC COLOURS/RAINBOW
7	REMOTE RESET

• **DIMENSION (WxDxH max)**
mm 480x490x740

• **WEIGHT**
Kgs. 31,0