

- 
- Heat-resistant, dual reflecting surfaces
 - Broad opening for even, shadowless illumination
 - Scientifically-curved, color-corrected reflecting surfaces for broad, soft, even illumination
 - Easy, secure tilt adjustment (without tools) with cool, heat-resistant phenolic knobs
 - Two dual socket assemblies, each accepting choice of three lamp wattages
 - Double color frame grooves for diffusion and color mixing
 - Cable chain supports slack or excess cable neatly
 - Durable gray wrinkle finish
 - Ventilated sheet steel housing
 - Strong steel yoke
 - Available with stand adaptor, C-clamp, or both

Kliegl Softlights[®] are designed to soften or eliminate shadows and provide broad, even, diffused illumination. Typical applications in video, still and cine studios include: soft, unobtrusive fill light which lowers contrasts, virtually shadowless illumination, color correcting of sets and use as an artificial "window" light for portrait, product and glamour work. When used in a bank, Softlights[®] simulate north skylight illumination at 3200°K. Built-in flexibility widens the range of applications. Both sockets accept 1000, 1500 or 2000 Watt, long-life tungsten-

6914
MODEL

KLIEGL SOFLIGHT®

Specifications

Accessories

16914	Color Frame
1421	25" Rolling Castered Stand
11720DS	Double scrim diffuser frame
1850	C-clamp
110	Safety cable

Connectors

955G	2-pole, 3-wire 20A Pin Connector
TLG	2-pole, 3-wire Twistlock (LP-20P)

(All configurations are UL listed.)

Lamp Information

ANSI Code	Watts	Color Temp.	Avg. Rated Life (hrs.)	Nom. Lumens
FFW	2000	3200°K	125	57,000
FOB	1500	3200°K	400	41,000
FFT	1000	3200°K	300	27,000

UL Listed and Labeled
Union Made in the U.S.A.

Design subject to change
without notification.

Kliegl 2000-4000 WATT
SOFLIGHT®

kliegl
Kleigl Bros.

32-32 48th Avenue
Long Island City, New York 11101
212/786-7474 Telex: 950158

©1979 Kliegl Bros. Printed in U.S.A.